

Fluorine Free Foam Wheeled Extinguisher 150 liters AB (cartridge)

Wheeled extinguisher is designed for professional use under severe circumstances, resulting in a high level of quality and ease of use. The cylinder, CE marked, has the welded frame. Ease of mobility is achieved as a result of the large wheels with solid rubber tyres and push bar also ensuring good stability during operation.



Applications for marine, inland shipping and offshore market

- engine rooms
- car decks
- heli decks

Body

AISI 304L stainless steel cylinder, red polyester powder painted. Manufactured according to EN 1866-1 and the Directive 2014/68/EU (PED). Compact model with all accessories welded on the main cylinder.

Valve

Nickel-plated brass head cap with safety valve. Pressure gauge to check the pressurization status and Schrader valve to release pressure before opening.

Cartridge

Nitrogen N2 steel bottle, black painted, certified to 2010/35/UE. Handwheel brass valve with safety device.

Extinguishing agent

Extinguisher based on water with additives, 100% FLUORINE FREE. Designed to guarantee excellent performance on class A and B fires while respecting the environment. All parts in contact with the extinguishant are compatible.

Hose and Horn

EPDM reinforced rubber hose, 5 meter, with polyamide PA6 squeeze pistol; it guarantees perfect flexibility within the temperature range.

TECHNICAL SPECIFICATIONS

Manufacturer / Model	ABS
Extinguisher	AFFF Foam, PFAS Free
Cylinder	External painting: Polyester Resin Corrosion resistance: 480 H SECONDO ISO 9227:2017
Capacity	150 liter
Fire class / Rating	A IVB
Propellant gas	N ₂
Discharge time	720 seconds
Throw length	8 meters
Working pressure	13 bar at 20°C
Extinguishing agent	AFFF Foam Fluorine Free
Length discharge hose	5 meters
Diameter wheels	400 mm
Temperature range	+5°C to +60°C
Approx gross weight	80 kgs
Approx dispatch weight	230 kgs
Approx unit dimension	900 x 700 x 1380 mm (l x w x h)
Color	Cylinder red
Approvals	EN 1866 / CE, MED

